



KAIKOURA / 5748

Style	Solution Dyed Hardtwist Cut Pile
Pile Content	100% Solution Dyed Nylon
Width	3.66m Broadloom
Carpet Thickness	11.0 mm +/- 10%
Grading	Residential Extra Heavy Duty + Stairs 6 Stars ACCS (11214) Contract Heavy Duty + Stairs 3 Stars ACCS (11214)
Construction	Tufted
Environmental Accreditation	ACCS ECS: Level 4
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Jute
Pattern Repeat	None

CAUTION – Shading On Cut Pile Carpet: All cut pile carpets will in some circumstances exhibit the condition known as “Shading, Watermarking, or Pile Reversal”. This condition is characterised by random light and dark patches appearing some weeks after installation, caused by the permanent reversal or bending of the carpet pile fibres with consequential different light effects. It cannot be predicted or prevented and appears to be related to the location of use rather than type of carpet construction or materials used. It does not affect the wear or durability of the carpet and since it is beyond the control of the manufacturer, it is not recognised as a manufacturing flaw or fault. You are urged to consider this characteristic before purchasing. Your Sales Executive can provide further information.

Installation, Cleaning and Maintenance: This carpet must be installed in accordance with AS/NZS 2455.1:2007 unless otherwise specified. Cleaning and maintenance must be done in accordance with AS/NZS 3733:1995.

Colour Variation: Colour may vary from dye lot to dye lot.

Material Variation: Backing or other materials may change without notice depending on raw material availability.

Custom Variation: Custom weights and/or colours may be produced to meet individual requirements for larger projects. For further details contact your local Norman Ellison office.